

G&G Controls

Twin pump wastewater control panel

Features:

- Hand/Off/Auto control for each pump
- High level alarm with sounder c/w power supplies for 2no. remote beacons
- Volt-free output relays for pump running, pump fault and high-level alarm
- Lifetime warranty on the switching relay
- Available in either powder-coated mild steel enclosure or polyester reinforced with fibreglass (stainless steel available at extra cost)
- Direct-on-line as standard
- Interlocked power isolator with shaft guide to ensure isolator shaft always aligns with door handle
- Supplied in bespoke packaging to prevent damage in transit



Optional Extras:

- Ammeters for each pump
- Hours run indication for each pump
- Generator inlet
- Seal leak relay and lamp
- Ultrasonic level controls with touchscreen display
- Panel heater with thermostat
- 230v socket for auxiliary supply (laptop charging, etc)
- Power failure alarm (battery operated)
- Spring-back switches

| | |
|---------------------------|---|
| Input Voltage | 230vac |
| Current Rating (per pump) | 1 - 18 amps (specify when ordering) |
| Control circuit | 24vac |
| Enclosure material | Powder coated mild steel (Also available in polyester reinforced with fibreglass) |
| Warranty | 12 months (lifetime warranty on alternating relay) |
| Dimensions | 500mm high x 400mm wide x 200mm deep |
| Degree of protection | IP65 |