

G&G Controls

Twin pump wastewater control panel

Features:

- Hand/Off/Auto control for each pump
- High level alarm with sounder c/w power supplies for 2no. remote beacons
- Start & run capacitors (uF capacity TBC)
- Volt-free output relays for pump running, pump fault and high-level alarm
- Lifetime warranty on the switching relay
- Available in either powder-coated mild steel enclosure or polyester reinforced with fibreglass (stainless steel available at extra cost)
- Direct-on-line
- Interlocked power isolator with shaft guide to ensure isolator shaft always aligns with door handle
- Supplied in bespoke packaging to prevent damage in transit



Optional Extras:

- Ammeters for each pump
- Hours run indication for each pump
- Generator inlet
- Seal leak relay and lamp
- Ultrasonic level controls with touchscreen display
- Panel heater with thermostat
- 230v socket for auxiliary supply (laptop charging, etc)
- Power failure alarm (battery operated)
- Spring-back switches

Input Voltage	230vac
Current Rating (per pump)	1 - 18 amps (specify when ordering)
Control circuit	24vac
Enclosure material	Powder coated mild steel (Also available in polyester reinforced with fibreglass)
Warranty	12 months (lifetime warranty on alternating relay)
Dimensions	600mm high x 400mm wide x 200mm deep
Degree of protection	IP65